



FTBx-88260 Report

| K-20 Layer 2 Test

FAIL

Report Header:	EXFO Inc.
Report Title:	K-20 Layer 2 Test
Report Date:	3/26/2025 11:11:09 AM
Type:	EtherSAM (Y.1564)

Job Information

Job ID:	
Circuit ID:	Lumen:04/KXGS/412636//PN
Contractor Name:	K-20 Networks
Customer Name:	Spokane-k12
Operator Name:	kithc
Comment:	

Table of contents

SUMMARY	1
TEST RESULTS	9
TEST SETUP	11
FUNCTIONS	17
SYSTEM INFORMATION	22
LOGGER	26

SUMMARY

Results Summary

Test Status	
Service Configuration Test Status	Completed, Fail
Service Performance Test Status	Completed, Fail
Pass/Fail Verdict	FAIL
Start Time	3/26/2025 11:02:58 AM
Duration	00d:00:06:29
Test Recovery	0

EtherSAM

Services Summary			
	Service Name	Service Configuration Test	Service Performance Test
1	Service 1	FAIL	FAIL

Service Configuration Summary							
	Service Name	Direction	Frame Loss Rate	Max Jitter (ms)	Max Latency (ms)	Max Throughput (Mbit/s)	Service Verdict
1	Service 1	L->R	2.2E-01	0.00575		40736.2	FAIL
		R->L	1.9E-01	< 0.00001	7.46711	40754.6	FAIL

Service Performance Summary							
	Service Name	Direction	Frame Loss Rate	Max Jitter (ms)	Max Latency (ms)	Avg Throughput (Mbit/s)	Service Verdict
1	Service 1	L->R	--	--		--	FAIL
		R->L	1.9E-01	< 0.00001	7.47838	40750.1	FAIL

VLAN Preservation	No Mismatch Detected
--------------------------	----------------------

RX Power Level		
	Min	Max
Power Range (dBm)	-10.60	4.50
Optical Lane	RX Power Level (dBm)	
	Min	Max
0	0.83	0.94
1	0.40	0.51
2	0.95	1.05
3	-0.55	-0.38

RX Frequency		
CAUI-4 Lane	Frequency Offset (ppm)	
	Max Negative Offset	Max Positive Offset
0	0.0	0.8
1	0.0	0.8
2	0.0	0.8
3	0.0	0.8

Alarms/Errors

Alarms/Errors List	
Active/Historical Alarms/Errors	Frame Loss

Interface				
Optical Lane	LOS	CAUI-4 Lane	LOC Lane	Frequency
	Seconds		Seconds	Seconds
0	0	0	0	0
1	0	1	0	0
2	0	2	0	0
3	0	3	0	0

Ethernet			
Alarms	Seconds		
Link Down	0		
Local Fault Detected	0		
Local Fault Received	0		
Remote Fault	0		
Hi-BER	0		

Errors	Seconds	Count	Rate
FCS	0	0	0.00E00
Jabber	0	0	0.00E00
Oversize	Disabled		
Runt	0	0	0.00E00
Undersize	0	0	0.00E00
Total		0	

PCS Lanes	
Alarms	Seconds
LOA	0
Invalid Mapping	0

PCS Lanes			
PCS Lane	LOBL	LOAML	Excessive Skew
Alarms	Seconds	Seconds	Seconds
0	0	0	0
1	0	0	0
2	0	0	0
3	0	0	0
4	0	0	0
5	0	0	0
6	0	0	0
7	0	0	0
8	0	0	0
9	0	0	0
10	0	0	0
11	0	0	0
12	0	0	0
13	0	0	0
14	0	0	0
15	0	0	0
16	0	0	0
17	0	0	0
18	0	0	0
19	0	0	0

Skew Alarm Threshold (bits)	928
-----------------------------	-----

PCS Lanes						
PCS Lane Errors	Block			Inv. Marker		
	Seconds	Count	Rate	Seconds	Count	Rate
0	0	0	0.00E00	0	0	0.00E00
1	0	0	0.00E00	0	0	0.00E00
2	0	0	0.00E00	0	0	0.00E00
3	0	0	0.00E00	0	0	0.00E00
4	0	0	0.00E00	0	0	0.00E00
5	0	0	0.00E00	0	0	0.00E00
6	0	0	0.00E00	0	0	0.00E00
7	0	0	0.00E00	0	0	0.00E00
8	0	0	0.00E00	0	0	0.00E00
9	0	0	0.00E00	0	0	0.00E00
10	0	0	0.00E00	0	0	0.00E00
11	0	0	0.00E00	0	0	0.00E00
12	0	0	0.00E00	0	0	0.00E00
13	0	0	0.00E00	0	0	0.00E00
14	0	0	0.00E00	0	0	0.00E00
15	0	0	0.00E00	0	0	0.00E00
16	0	0	0.00E00	0	0	0.00E00
17	0	0	0.00E00	0	0	0.00E00
18	0	0	0.00E00	0	0	0.00E00
19	0	0	0.00E00	0	0	0.00E00

PCS Lanes			
PCS Lane Errors	BIP-8		
	Seconds	Count	Rate
0	0	0	0.00E00
1	0	0	0.00E00
2	0	0	0.00E00
3	0	0	0.00E00
4	0	0	0.00E00
5	0	0	0.00E00
6	0	0	0.00E00
7	0	0	0.00E00
8	0	0	0.00E00
9	0	0	0.00E00
10	0	0	0.00E00
11	0	0	0.00E00
12	0	0	0.00E00
13	0	0	0.00E00
14	0	0	0.00E00
15	0	0	0.00E00
16	0	0	0.00E00
17	0	0	0.00E00
18	0	0	0.00E00
19	0	0	0.00E00

Clock Sync	
Alarm	Seconds
LOC	0

IP/UDP			
Errors	Seconds	Count	Rate
IP Checksum	0	0	0.00E00
UDP Checksum	0	0	0.00E00
Total		0	

Setup Summary

Application Type	EtherSAM (Y.1564)
------------------	-------------------

Topology	Single Port
----------	-------------

Interface	Port B1
Interface/Rate	100GE (4 Lanes) [103.125 Gbit/s]
PHY Type	LR4/ER4
Connector	QSFP28

Flow Control	None
--------------	------

EtherSAM

DTS Enabled	
Remote ID	--
Nat Router Detection	--
Local WAN IP	N/A
Pass/Fail Verdict	Enabled

Sub-Tests

Service Configuration Test		Service Performance Test	
L2CP Handling Test	Disabled	Status	Enabled
Ramp Test	Enabled	Duration	00d:00:10:00
Burst selection	Disabled		
Duration	00:00:20		

Ramp

Step Time (s)	5
Step Values	
1	50 %
2	75 %
3	90 %
4	100 %

Services

Total Committed TX Rate (Mbit/s)	L->R	50000.0
	R->L	50000.0

Services Summary

	Service Name	Profile	Frame Size (Bytes)	Direction	CIR (Mbit/s)	Max Jitter (ms)	Max Latency (ms)	Frame Loss Rate	CBS (Bytes)
1	Service 1	Data	Random	L->R	50000.0	2.00000		1.0E-04	--
				R->L	50000.0	2.00000	28.00000	1.0E-04	

TEST RESULTS

Ethernet Traffic

Frame Type	TX Count	RX Count
Multicast	0	14
Broadcast	5	5
Unicast	2776123793	2247138354
Non-Unicast	5	19
Total	2776123798	2247138373

Frame Size (Bytes)	RX Count	%
< 64	0	0.0
64	309	0.0
65 - 127	89170646	3.9
128 - 255	189366554	8.4
256 - 511	386034539	17.1
512 - 1023	789311361	35.1
1024 - 1518	793254964	35.3
> 1518	0	0.0
Total	2247138373	

Detailed EtherSAM Results

Service Configuration Test**Service 1 : Service 1**

Committed Steps						
Committed Step	Direction	Frame Loss Rate	Max Jitter (ms)	Max Latency (ms)	Verdict	Avg Throughput (Mbit/s)
1-50%CIR	L->R	0.0E-00	0.00575	7.46711	PASS	24999.9
	R->L	0.0E-00	< 0.00001		PASS	24999.9
2-75%CIR	L->R	0.0E-00	0.00415	7.46338	PASS	37499.9
	R->L	0.0E-00	< 0.00001		PASS	37500.0
3-90%CIR	L->R	1.2E-01	0.00395	7.46633	FAIL	40736.2
	R->L	1.0E-01	< 0.00001		FAIL	40754.6
CIR	L->R	2.2E-01	0.00406	7.46560	FAIL	40725.9
	R->L	1.9E-01	< 0.00001		FAIL	40750.0

Service Performance Test

Service 1 : Service 1

	Direction	Average	Minimum	Maximum	Estimate
Throughput (Mbit/s)	L->R	--	--	--	N/A
	R->L	40750.1	40749.6	40750.7	N/A
Jitter (ms)	L->R	--	--	--	--
	R->L	< 0.00001	< 0.00001	< 0.00001	< 0.00001
Latency (ms)	Round-trip	7.45268	7.43875	7.47838	N/A
		Seconds	Count	Rate	
Frame Loss	L->R	--	--	--	
	R->L	303	459072590	1.9E-01	
Out-of-Sequence	L->R	--	--	--	
	R->L	0	0	0.0E00	

TEST SETUP

Clock Synchronization	
Clock Mode	Internal

Detailed L2CP Frames Configuration

	Name	Type	Frame Format	Destination MAC Address
0	STP	STP	LLC	01:80:C2:00:00:00
1	RSTP	RSTP	LLC	01:80:C2:00:00:00
2	MSTP	MSTP	LLC	01:80:C2:00:00:00
3	LACP	LACP	Ethernet II	01:80:C2:00:00:00
4	LAMP	LAMP	Ethernet II	01:80:C2:00:00:00
5	LLDP	LLDP	Ethernet II	01:80:C2:00:00:00
6	VDP	VDP	Ethernet II	01:80:C2:00:00:00
7	802.1X	802.1X	Ethernet II	01:80:C2:00:00:00
8	SPB	SPB	LLC	01:80:C2:00:00:2E
9	MMRP	MMRP	Ethernet II	01:80:C2:00:00:20
10	MVRP	MVRP	Ethernet II	01:80:C2:00:00:21
11	MIRP	MIRP	Ethernet II	01:80:C2:00:00:00
12	Link-OAM	Link-OAM	Ethernet II	01:80:C2:00:00:02
13	ESMC	ESMC	Ethernet II	01:80:C2:00:00:02
14	PTP	PTP	Ethernet II	01:80:C2:00:00:0E
15	ELMI	E-LMI	Ethernet II	01:80:C2:00:00:07
16	PE-CSP	PE-CSP	Ethernet II	01:80:C2:00:00:03
17	MAC-PAUSE	MAC-PAUSE	Ethernet II	01:80:C2:00:00:01
18	MAC-PFC	MAC-PFC	Ethernet II	01:80:C2:00:00:01
19	MPMAC-Gate	MPMAC-Gate	Ethernet II	01:80:C2:00:00:01
20	MPMAC-Report	MPMAC-Report	Ethernet II	01:80:C2:00:00:01
21	MPMAC-Register-req	MPMAC-Register-req	Ethernet II	01:80:C2:00:00:01
22	MPMAC-Register	MPMAC-Register	Ethernet II	01:80:C2:00:00:01
23	MPMAC-Register-ack	MPMAC-Register-ack	Ethernet II	01:80:C2:00:00:01
24	MAC-Org-Spec-Ext	MAC-Org-Spec-Ext	Ethernet II	01:80:C2:00:00:01
25	MSRP	MSRP	Ethernet II	01:80:C2:00:00:0E
26	CDP	CDP	SNAP	01:00:0C:CC:CC:CC
27	VTP	VTP	SNAP	01:00:0C:CC:CC:CC
28	PAgP	PAgP	SNAP	01:00:0C:CC:CC:CC
29	UDLD	UDLD	SNAP	01:00:0C:CC:CC:CC
30	DTP	DTP	SNAP	01:00:0C:CC:CC:CC
31	PVST+(LLC)	PVST+(LLC)	LLC	01:00:0C:CC:CC:CD

32	PVST+(SNAP)	PVST+(SNAP)	SNAP	01:00:0C:CC:CC:CD
33	STP-ULFAST	STP-ULFAST	LLC	01:00:0C:CD:CD:CD
34	VLAN-BRDSTP	VLAN-BRDSTP	LLC	01:00:0C:CD:CD:CE
35	ISL	ISL	SNAP	01:00:0C:00:00:00
36	GMRP	GMRP	LLC	01:80:C2:00:00:20
37	GVRP	GVRP	LLC	01:80:C2:00:00:21
38	User 1 (01-80-C2)	User (01-80-C2)	Ethernet II	01:80:C2:00:00:00
39	User 2 (01-80-C2)	User (01-80-C2)	Ethernet II	01:80:C2:00:00:00
40	User 3 (01-80-C2)	User (01-80-C2)	Ethernet II	01:80:C2:00:00:00
41	User 4 (01-80-C2)	User (01-80-C2)	Ethernet II	01:80:C2:00:00:00
42	User 5 (01-00-0C)	User (01-00-0C)	Ethernet II	01:00:0C:00:00:00
43	User 6 (01-00-0C)	User (01-00-0C)	Ethernet II	01:00:0C:00:00:00
44	User 7 (01-00-0C)	User (01-00-0C)	Ethernet II	01:00:0C:00:00:00
45	User 8 (01-00-0C)	User (01-00-0C)	Ethernet II	01:00:0C:00:00:00

	LLC	OUI	EtherType	Subtype	Custom Bytes	Frame Size
0	0x424203					64
1	0x424203					64
2	0x424203					64
3			0x8809	0x01		128
4			0x8809	0x02		128
5			0x88CC			64
6			0x8940	0x0001		64
7			0x888E			64
8	0xFEFE03					64
9			0x88F6			64
10			0x88F5			64
11			0x8929			64
12			0x8809	0x03		64
13			0x8809	0x0A		64
14			0x88F7			64
15			0x88EE			64
16			0x8940	0x0002		64
17			0x8808	0x0001		64
18			0x8808	0x0101		64
19			0x8808	0x0002		64
20			0x8808	0x0003		64
21			0x8808	0x0004		64
22			0x8808	0x0005		64
23			0x8808	0x0006		64
24			0x8808	0xFFFE		64
25			0x22EA			64
26	0xAAAA03	0x00000C	0x2000			64
27	0xAAAA03	0x00000C	0x2003			64

28	0xAAAA03	0x00000C	0x0104			88
29	0xAAAA03	0x00000C	0x0111			64
30	0xAAAA03	0x00000C	0x2004			64
31	0x424203					64
32	0xAAAA03	0x00000C	0x010B			68
33	0x424203					64
34	0x424203					64
35	0xAAAA03	0x00000C	0x0003			94
36	0x424203					64
37	0x424203					64
38			0x0600		0x0000000000000000 0000000000000000	64
39			0x0600		0x0000000000000000 0000000000000000	64
40			0x0600		0x0000000000000000 0000000000000000	64
41			0x0600		0x0000000000000000 0000000000000000	64
42			0x0600		0x0000000000000000 0000000000000000	64
43			0x0600		0x0000000000000000 0000000000000000	64
44			0x0600		0x0000000000000000 0000000000000000	64
45			0x0600		0x0000000000000000 0000000000000000	64

Detailed Services Configuration

IP Version	IPv4	
Layer Mode	Mixed	
Global Pass/Fail Verdict	Enabled	
	L->R	R->L
Total Committed TX Rate (Mbit/s)	50000.0	50000.0

Service 1

Service Profile	
Service Name	Service 1
Profile	Data
Frame Size Type	Random

SLA Parameters		
	L->R	R->L
Information Rate		
CIR (Mbit/s)	50000.0	50000.0
Performance Criteria		
Max Jitter (ms)	2.00000	2.00000
Max Latency (ms)	28.00000	28.00000
Frame Loss Rate	1.0E-04	1.0E-04

Test Parameters		
	L->R	R->L

Framing		
Frame Format	Ethernet II	
Network Layer	IPv4	
Transport Layer	UDP	
	L->R	R->L
VLAN	None	None

Addressing

		MAC	IP Address	UDP Port
L->R	Source	00:03:01:F8:30:CF	10.112.0.1 / 255.255.255.0	49184
	Destination	00:03:01:13:99:87	10.112.0.100	7
R->L	Source	00:03:01:13:99:87	10.112.0.100 / 255.255.255.0	7
	Destination	00:03:01:F8:30:CF	10.112.0.1	49184

	L->R	R->L
EtherType	0x0800	0x0800
Automatic IP (DHCP)	Disabled	Disabled
TTL	128	128
TOS	0x00	0x00
Default Gateway	Disabled	Disabled

L2CP Handling Test		
Name	Destination MAC Address	Expected L2CP Handling
STP	01:80:C2:00:00:00	Pass Through
RSTP	01:80:C2:00:00:00	Pass Through
MSTP	01:80:C2:00:00:00	Pass Through
LACP	01:80:C2:00:00:00	Pass Through
LAMP	01:80:C2:00:00:00	Pass Through
LLDP	01:80:C2:00:00:00	Pass Through
VDP	01:80:C2:00:00:00	Pass Through
802.1X	01:80:C2:00:00:00	Pass Through
SPB	01:80:C2:00:00:2E	Pass Through
MMRP	01:80:C2:00:00:20	Pass Through
MVRP	01:80:C2:00:00:21	Pass Through
MIRP	01:80:C2:00:00:00	Pass Through
Link-OAM	01:80:C2:00:00:02	Pass Through
ESMC	01:80:C2:00:00:02	Pass Through
PTP	01:80:C2:00:00:0E	Pass Through
ELMI	01:80:C2:00:00:07	Pass Through
PE-CSP	01:80:C2:00:00:03	Pass Through
MAC-PAUSE	01:80:C2:00:00:01	Pass Through
MAC-PFC	01:80:C2:00:00:01	Pass Through
MPMAC-Gate	01:80:C2:00:00:01	Pass Through
MPMAC-Report	01:80:C2:00:00:01	Pass Through
MPMAC-Register-req	01:80:C2:00:00:01	Pass Through
MPMAC-Register	01:80:C2:00:00:01	Pass Through
MPMAC-Register-ack	01:80:C2:00:00:01	Pass Through
MAC-Org-Spec-Ext	01:80:C2:00:00:01	Pass Through
MSRP	01:80:C2:00:00:0E	Pass Through
CDP	01:00:0C:CC:CC:CC	Pass Through
VTP	01:00:0C:CC:CC:CC	Pass Through
PAgP	01:00:0C:CC:CC:CC	Pass Through
UDLD	01:00:0C:CC:CC:CC	Pass Through
DTP	01:00:0C:CC:CC:CC	Pass Through
PVST+(LLC)	01:00:0C:CC:CC:CD	Pass Through
PVST+(SNAP)	01:00:0C:CC:CC:CD	Pass Through

STP-ULFAST	01:00:0C:CD:CD:CD	Pass Through
VLAN-BRDSTP	01:00:0C:CD:CD:CE	Pass Through
ISL	01:00:0C:00:00:00	Pass Through
GMRP	01:80:C2:00:00:20	Pass Through
GVRP	01:80:C2:00:00:21	Pass Through

FUNCTIONS

40/100G Advanced

Lanes Mapping & Skew

TX		CAUI-4 Lane	RX	
PCS Lane	Skew (bits)		Skew (bits)	PCS Lane
0	0	0	17	3
1	0		17	4
2	0		16	0
3	0		16	1
4	0	1	16	2
5	0		1	7
6	0		1	8
7	0		1	9
8	0	2	0	5
9	0		0	6
10	0		29	10
11	0		29	11
12	0	3	29	12
13	0		29	13
14	0		29	14
15	0		6	18
16	0		6	19
17	0		5	15
18	0		5	16
19	0		5	17

PCS Lanes			
PCS Lane	LOBL	LOAML	Excessive Skew
Alarms	Seconds	Seconds	Seconds
0	0	0	0
1	0	0	0
2	0	0	0
3	0	0	0
4	0	0	0
5	0	0	0
6	0	0	0
7	0	0	0
8	0	0	0
9	0	0	0
10	0	0	0
11	0	0	0
12	0	0	0
13	0	0	0
14	0	0	0
15	0	0	0
16	0	0	0
17	0	0	0
18	0	0	0
19	0	0	0

Skew Alarm Threshold (bits)	928
-----------------------------	-----

PCS Lanes						
PCS Lane	Block			Inv. Marker		
Errors	Seconds	Count	Rate	Seconds	Count	Rate
0	0	0	0.00E00	0	0	0.00E00
1	0	0	0.00E00	0	0	0.00E00
2	0	0	0.00E00	0	0	0.00E00
3	0	0	0.00E00	0	0	0.00E00
4	0	0	0.00E00	0	0	0.00E00
5	0	0	0.00E00	0	0	0.00E00
6	0	0	0.00E00	0	0	0.00E00
7	0	0	0.00E00	0	0	0.00E00
8	0	0	0.00E00	0	0	0.00E00
9	0	0	0.00E00	0	0	0.00E00
10	0	0	0.00E00	0	0	0.00E00
11	0	0	0.00E00	0	0	0.00E00
12	0	0	0.00E00	0	0	0.00E00
13	0	0	0.00E00	0	0	0.00E00
14	0	0	0.00E00	0	0	0.00E00
15	0	0	0.00E00	0	0	0.00E00
16	0	0	0.00E00	0	0	0.00E00
17	0	0	0.00E00	0	0	0.00E00
18	0	0	0.00E00	0	0	0.00E00
19	0	0	0.00E00	0	0	0.00E00

PCS Lanes				
PCS Lane	BIP-8			
	Errors	Seconds	Count	Rate
0	0	0	0	0.00E00
1	0	0	0	0.00E00
2	0	0	0	0.00E00
3	0	0	0	0.00E00
4	0	0	0	0.00E00
5	0	0	0	0.00E00
6	0	0	0	0.00E00
7	0	0	0	0.00E00
8	0	0	0	0.00E00
9	0	0	0	0.00E00
10	0	0	0	0.00E00
11	0	0	0	0.00E00
12	0	0	0	0.00E00
13	0	0	0	0.00E00
14	0	0	0	0.00E00
15	0	0	0	0.00E00
16	0	0	0	0.00E00
17	0	0	0	0.00E00
18	0	0	0	0.00E00
19	0	0	0	0.00E00

Ping & Trace Route

Network	
Source MAC Address	00:03:01:F8:30:CF
Source IP Address	10.112.0.1 (Stream 1)
Destination IP Address	10.112.0.100

Ping	
Timeout (ms)	4000
Delay (ms)	1000
Data Size (Bytes)	32
TTL	128
Type Of Service (TOS)	0x00

Ping Results		
No.	Status	Reply Details
1	Timeout	
2	Timeout	
3	Timeout	
4	Timeout	
5	Timeout	
6	Timeout	
7	Timeout	
8	Timeout	
9	Timeout	
10	Timeout	
11	Timeout	
12	Timeout	
13	Timeout	
14	Timeout	
15	Successful	IP=10.112.0.100, Bytes=32, Time=16 ms, TTL=127
16	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
17	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
18	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
19	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
20	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
21	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
22	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
23	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
24	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
25	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
26	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
27	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
28	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
29	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
30	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
31	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
32	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
33	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127

34	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
35	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
36	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
37	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
38	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
39	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
40	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
41	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
42	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
43	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
44	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
45	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
46	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
47	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
48	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
49	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
50	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
51	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
52	Successful	IP=10.112.0.100, Bytes=32, Time=7 ms, TTL=127
53	User aborted	

Ping Statistics

Packets Transmitted	52
Packets Received	38
Percentage Lost (%)	26.9
Minimum Round Trip Time (ms)	7
Maximum Round Trip Time (ms)	16
Average Round Trip Time (ms)	7

Trace Route

Timeout (ms)	1000
Max Hop Count	128

SYSTEM INFORMATION

Product Name	Power Blazer Series
Version	Power Blazer Series 1.124
Module ID	FTBx-88260
Slot ID	2
Software Product Version	1.124.0.53
	Power Blazer Series 1.124
Assembly Hardware Revision	A
Serial Number	1347374
Calibration Date	4/21/2020 1:22:00 PM

Transceiver System

Transceiver System Insertion Counter	49
ID	TA-QSFP28
Serial Number	1350527
Revision	A
Battery	Good
Optical Module Insertion Counter	34

Pluggable Module

Module ID	QSFP28 or later
Vendor Name	JUNIPER-1W1
Part Number	1W1QAA
Serial Number	1W1CQAA9410SQ
Hardware Revision	01
Revision Compliance	7
Connector Type	LC
Speed	25G, 103.125 Gbit/s
Type/Compliance Code	LR, 100GE-LR4-10km, 10.0 km
Mode	Single-Mode Fiber, SMF
Power Class	Power Class 4 (<= 3.5W)
Temperature (Max)	38.5 °C
CLEI Code	

Software Options

100electrical	Ethernet 100Base-TX (Electrical) Interface	Enabled
100GE	Ethernet 100G	Enabled
100optical	Ethernet 100Base-FX (Optical) Interface	Enabled
10electrical	Ethernet 10Base-T (Electrical) Interface	Enabled
10G_LAN	Ethernet 10G LAN (Optical) and 10GBASE-T (Electrical) interfaces	Enabled
10G_WAN	Ethernet 10G WAN optical interface	Enabled
155M	155 Mbit/s	Enabled
1588PTP	1588 Precision Time Protocol	Enabled
1588PTPGM	1588 Precision Time Protocol Grandmaster Emulation	Enabled
2.5-5GE	Ethernet 2.5GBASE-T and 5GBASE-T (Electrical) interfaces	Enabled
2488M	2.488 Gbit/s	Enabled
25GE	Ethernet 25G	Enabled
40GE	Ethernet 40G	Enabled

50GE	Ethernet 50G	Enabled
52M	52 Mbit/s	Enabled
622M	622 Mbit/s	Enabled
9953M	9.953 Gbit/s	Enabled
CPRI	CPRI 2.4576 Gbit/s and 3.072 Gbit/s	Enabled
CPRI-1.2G	CPRI 1.2288 Gbit/s	Enabled
CPRI-10.1G	CPRI 10.1376 Gbit/s	Enabled
CPRI-24.3G	CPRI 24.33024 Gbit/s	Enabled
CPRI-4.9G	CPRI 4.9152 Gbit/s	Enabled
CPRI-6.1G	CPRI 6.144 Gbit/s	Enabled
CPRI-9.8G	CPRI 9.8304 Gbit/s	Enabled
DCO-100ZR	100ZR	Enabled
DSn	Digital Signal (DS1, DS3)	Enabled
eCPRI-100G	eCPRI over 100G Ethernet	Enabled
eCPRI-10G	eCPRI over 10G Ethernet	Enabled
eCPRI-25G	eCPRI over 25G Ethernet	Enabled
EoE	Ethernet over Ethernet Encapsulation (10GE and less)	Enabled
EoE_40-100GE	Ethernet over Ethernet Encapsulation (40/100GE)	Enabled
EoOTN	Ethernet over Optical Transport Network	Enabled
ETH-OAM	Carrier Ethernet OAM Test Application	Enabled
FC-10X	Fibre Channel 10X	Enabled
FC-16X	Fibre Channel 16X	Enabled
FC-1X	Fibre Channel 1X	Enabled
FC-2X	Fibre Channel 2X	Enabled
FC-32X	Fibre Channel 32X	Enabled
FC-4X	Fibre Channel 4X	Enabled
FC-8X	Fibre Channel 8X	Enabled
FlexE-100G	100G FlexE Group	Enabled
FlexE-200G	200G FlexE Group	Enabled
FlexE-50G	50G FlexE Group	Enabled
FlexE-50G-PHY	FlexE 50G Interface Type	Enabled
FlexE-HiRateClient	FlexE Clients at 150G and above	Enabled
FlexE-LoRateClient	FlexE Clients at 100G and below	Enabled
FlexE-MIX	FlexE Clients at mixed rates	Enabled
G.mtnPathOAM	G.mtn Path OAM	Enabled
GCC-BERT	OTN Overhead BERT and Synchronization Validation	Enabled
GigE_Electrical	Ethernet 1000Base-T (Electrical) Interface	Enabled
GigE_Optical	Ethernet 1000Base-X (Optical) Interface	Enabled
iOptics	Intelligent Pluggable Optic Test Application	Enabled
iSAM	Intelligent Service Activation Methodology	Enabled
L2-Transparency	L2CP Handling Test in EtherSAM	Enabled
LINK-OAM	Link OAM	Enabled
LLDP	LLDP Neighbor Discovery	Enabled
MPLS	MPLS Encapsulation (10GE and less)	Enabled
MPLS_40-100GE	MPLS Encapsulation (40/100GE)	Enabled
OBSAI	OBSAI 3.072 Gbit/s	Enabled

OBSAI-1.5G	OBSAI 1.536 Gbit/s	Enabled
OBSAI-6.1G	OBSAI 6.144 Gbit/s	Enabled
ODU0	OTN ODU0	Enabled
ODUflex	OTN ODUflex	Enabled
ODUMUX	ODU Multiplexing Payload Type 20 and 21	Enabled
OTN-INTR-THRU	OTN Intrusive Through Mode	Enabled
OTU1	Optical Transport Unit-1 (2.7 Gbit/s)	Enabled
OTU2	Optical Transport Unit-2 (10.7 Gbit/s)	Enabled
OTU2-1e-2e	Optical Transport Unit-2 Overclocked (11.049/11.096 Gbit/s)	Enabled
OTU2-1f-2f	Optical Transport Unit-2 Overclocked (11.270/11.317 Gbit/s)	Enabled
OTU3	Optical Transport Unit-3 (43.018 Gbit/s)	Enabled
OTU3-e1-e2	Optical Transport Unit-3 Overclocked (44.571/44.583 Gbit/s)	Enabled
OTU4	Optical Transport Unit-4 (111.81 Gbit/s)	Enabled
Packet-TE	Packet Time Error	Enabled
PBBTE	Provider Backbone Bridge Encapsulation (10GE and less)	Enabled
PBBTE_40-100GE	Provider Backbone Bridge Encapsulation (40/100GE)	Enabled
PDH	Plesiochronous Digital Hierarchy (E1, E3, E4)	Enabled
RFC6349	RFC 6349 Test Application (25GE and less)	Enabled
RFC6349_40-100GE	RFC 6349 Test Application (40/100GE)	Enabled
SDH	Synchronous Digital Hierarchy	Enabled
SONET	Synchronous Optical Network	Enabled
SyncE	Synchronous Ethernet	Enabled
TCM	Tandem Connection Monitoring HO/LO	Enabled
TST-OAM	Test Over Service OAM	Enabled
WANDER	Time Error/Wander Test Application	Enabled

LOGGER

ID	Start Time	Event	Duration	Details
1	03/26 11:02:58 AM	Test Started		2025-03-26
2	03/26 11:03:03 AM	Service Configuration test started		2025-03-26
3	03/26 11:03:31 AM	Service 1 Fail		1 Service 1
4	03/26 11:03:37 AM	Service Performance test started		2025-03-26
5	03/26 11:03:42 AM	Frame Loss	00:05:46	459072590/459072590 S(1)
6	03/26 11:09:26 AM	RX Rate < 50000.0 Mbit/s	00:00:02	40750.1 Mbit/s S(1)
7	03/26 11:09:26 AM	Frame Loss > 1.0E-04	00:00:02	1.9E-01 S(1)
8	03/26 11:09:26 AM	Service 1 Fail		1 Service 1
9	03/26 11:09:27 AM	Test Stopped		 FAIL