



# FTBx-8870 Report

FAIL

Report Header: EXFO Inc.  
Report Title:  
Report Date: 9/3/2021 11:12:01 AM  
Type: EtherSAM (Y.1564)

## Job Information

Job ID: RTASK1922340  
Circuit ID: Wave: 11/GUNI/041821  
Contractor Name:  
Customer Name: tumwater-k12  
Operator Name: kithc  
Comment:

---

**Table of contents**

|                          |    |
|--------------------------|----|
| SUMMARY .....            | 1  |
| TEST RESULTS .....       | 5  |
| TEST SETUP .....         | 6  |
| FUNCTIONS .....          | 9  |
| SYSTEM INFORMATION ..... | 9  |
| LOGGER .....             | 12 |

## SUMMARY

### Results Summary

| Test Status                       |                      |
|-----------------------------------|----------------------|
| Service Configuration Test Status | Completed, Fail      |
| Service Performance Test Status   | Completed, Fail      |
| Pass/Fail Verdict                 | FAIL                 |
| Start Time                        | 9/3/2021 10:50:54 AM |
| Duration                          | 00d:00:10:48         |
| Test Recovery                     | 0                    |

### EtherSAM

| Services Summary |              |                            |                          |
|------------------|--------------|----------------------------|--------------------------|
|                  | Service Name | Service Configuration Test | Service Performance Test |
| 1                | Service 1    | FAIL                       | FAIL                     |

| Service Configuration Summary |              |                 |                 |                  |                         |                 |
|-------------------------------|--------------|-----------------|-----------------|------------------|-------------------------|-----------------|
|                               | Service Name | Frame Loss Rate | Max Jitter (ms) | Max Latency (ms) | Max Throughput (Mbit/s) | Service Verdict |
| 1                             | Service 1    | 3.7E-02         | 0.03903         | 94.07684         | 8990.35                 | FAIL            |

| Service Performance Summary |              |                 |                 |                  |                         |                 |
|-----------------------------|--------------|-----------------|-----------------|------------------|-------------------------|-----------------|
|                             | Service Name | Frame Loss Rate | Max Jitter (ms) | Max Latency (ms) | Avg Throughput (Mbit/s) | Service Verdict |
| 1                           | Service 1    | 7.0E-02         | 0.03180         | 159.10768        | 8830.91                 | FAIL            |

|                          |                      |
|--------------------------|----------------------|
| <b>VLAN Preservation</b> | No Mismatch Detected |
|--------------------------|----------------------|

| RX Power Level       |       |      |
|----------------------|-------|------|
|                      | Min   | Max  |
| Power Range (dBm)    | -19.0 | -1.0 |
| RX Power Level (dBm) | -2.2  | -2.1 |

| RX Frequency           |                     |                     |
|------------------------|---------------------|---------------------|
|                        | Max Negative Offset | Max Positive Offset |
| Frequency Offset (ppm) | 0.0                 | 0.0                 |

## Alarms/Errors

| Alarms/Errors List              |            |
|---------------------------------|------------|
| Active/Historical Alarms/Errors | Frame Loss |

| Interface |         |
|-----------|---------|
| Alarms    | Seconds |
| LOS       | 0       |
| Frequency | 0       |

| Ethernet             |         |
|----------------------|---------|
| Alarms               | Seconds |
| Link Down            | 0       |
| Local Fault Detected | 0       |
| Local Fault Received | 0       |
| Remote Fault         | 0       |

| Errors    | Seconds  | Count | Rate    |
|-----------|----------|-------|---------|
| Block     | 0        | 0     | 0.00E00 |
| FCS       | 0        | 0     | 0.00E00 |
| Jabber    | 0        | 0     | 0.00E00 |
| Oversize  | Disabled |       |         |
| Runt      | 0        | 0     | 0.00E00 |
| Undersize | 0        | 0     | 0.00E00 |
| Total     |          | 0     |         |

**Clock Sync**

| <b>Alarm</b> | <b>Seconds</b> |
|--------------|----------------|
| LOC          | 0              |

**IP/UDP/TCP**

| <b>Errors</b> | <b>Seconds</b> | <b>Count</b> | <b>Rate</b> |
|---------------|----------------|--------------|-------------|
| IP Checksum   | 0              | 0            | 0.00E00     |
| UDP Checksum  | 0              | 0            | 0.00E00     |
| TCP Checksum  | 0              | 0            | 0.00E00     |
| Total         |                | 0            |             |

## Setup Summary

|                         |                   |
|-------------------------|-------------------|
| <b>Application Type</b> | EtherSAM (Y.1564) |
|-------------------------|-------------------|

| Interface             | Port 1   |
|-----------------------|----------|
| <b>Interface/Rate</b> | 10GE LAN |
| <b>Connector</b>      | SFP+     |

|                     |      |
|---------------------|------|
| <b>Flow Control</b> | None |
|---------------------|------|

### EtherSAM

|                   |         |
|-------------------|---------|
| Pass/Fail Verdict | Enabled |
|-------------------|---------|

| Sub-Tests                  |          |                          |              |
|----------------------------|----------|--------------------------|--------------|
| Service Configuration Test |          | Service Performance Test |              |
| Ramp Test                  | Enabled  | Status                   | Enabled      |
| Burst selection            | Disabled | Duration                 | 00d:00:10:00 |
| Duration                   | 00:00:20 |                          |              |

| Ramp          |       |
|---------------|-------|
| Step Time (s) | 5     |
| Step Values   |       |
| 1             | 50 %  |
| 2             | 75 %  |
| 3             | 90 %  |
| 4             | 100 % |

### Services

|                                  |         |
|----------------------------------|---------|
| Total Committed TX Rate (Mbit/s) | 9500.00 |
|----------------------------------|---------|

| Services Summary |              |         |                    |              |                 |                  |                 |             |
|------------------|--------------|---------|--------------------|--------------|-----------------|------------------|-----------------|-------------|
|                  | Service Name | Profile | Frame Size (Bytes) | CIR (Mbit/s) | Max Jitter (ms) | Max Latency (ms) | Frame Loss Rate | CBS (Bytes) |
| 1                | Service 1    | Data    | Random             | 9500.00      | 2.00000         | 28.00000         | 1.0E-04         | --          |

## TEST RESULTS

### Ethernet Traffic

| Frame Type  | TX Count  | RX Count  |
|-------------|-----------|-----------|
| Multicast   | 0         | 24        |
| Broadcast   | 2         | 0         |
| Unicast     | 901609903 | 838905020 |
| Non-Unicast | 2         | 24        |
| Total       | 901609905 | 838905044 |

| Frame Size (Bytes) | RX Count  | %    |
|--------------------|-----------|------|
| < 64               | 0         | 0.0  |
| 64                 | 576745    | 0.0  |
| 65 - 127           | 36253846  | 4.3  |
| 128 - 255          | 73691614  | 8.7  |
| 256 - 511          | 147363699 | 17.5 |
| 512 - 1023         | 295112008 | 35.1 |
| 1024 - 1518        | 285907132 | 34.0 |
| > 1518             | 0         | 0.0  |
| Total              | 838905044 |      |

## Detailed EtherSAM Results

### Service Configuration Test

#### Service 1 : Service 1

| Committed Steps |                 |                 |                  |         |                         |
|-----------------|-----------------|-----------------|------------------|---------|-------------------------|
| Committed Step  | Frame Loss Rate | Max Jitter (ms) | Max Latency (ms) | Verdict | Avg Throughput (Mbit/s) |
| 1-50%CIR        | 0.0E-00         | 0.03903         | 2.92288          | PASS    | 4749.97                 |
| 2-75%CIR        | 0.0E-00         | 0.03465         | 3.74321          | PASS    | 7124.99                 |
| 3-90%CIR        | 0.0E-00         | 0.03058         | 13.42896         | PASS    | 8549.07                 |
| CIR             | 3.7E-02         | 0.02293         | 94.07684         | FAIL    | 8990.35                 |

### Service Performance Test

#### Service 1 : Service 1

|                     | Average  | Minimum   | Maximum   | Estimate |
|---------------------|----------|-----------|-----------|----------|
| Throughput (Mbit/s) | 8830.91  | 8617.55   | 9086.72   | N/A      |
| Jitter (ms)         | 0.00016  | < 0.00001 | 0.03180   | 0.00029  |
| Latency (ms)        | 98.44924 | 2.79416   | 159.10768 | N/A      |
|                     | Seconds  | Count     | Rate      |          |
| Frame Loss          | 596      | 61988779  | 7.0E-02   |          |
| Out-of-Sequence     | 0        | 0         | 0.0E00    |          |

## TEST SETUP

| Clock Synchronization |          |
|-----------------------|----------|
| Clock Mode            | Internal |

## Detailed Services Configuration

---

|                                  |         |
|----------------------------------|---------|
| Layer Mode                       | Mixed   |
| IP Version                       | IPv4    |
| Global Pass/Fail Verdict         | Enabled |
| Total Committed TX Rate (Mbit/s) | 9500.00 |

## Service 1

| Service Profile |           |
|-----------------|-----------|
| Service Name    | Service 1 |
| Profile         | Data      |
| Frame Size Type | Random    |

| SLA Parameters       |          |
|----------------------|----------|
| Information Rate     |          |
| CIR (Mbit/s)         | 9500.00  |
| Performance Criteria |          |
| Max Jitter (ms)      | 2.00000  |
| Max Latency (ms)     | 28.00000 |
| Frame Loss Rate      | 1.0E-04  |

## Test Parameters

| Framing         |             |
|-----------------|-------------|
| Frame Format    | Ethernet II |
| Network Layer   | IPv4        |
| Transport Layer | UDP         |
| VLAN            | None        |
| MPLS            | Disabled    |

## Addressing

|             | MAC               | IP Address                 | UDP Port |
|-------------|-------------------|----------------------------|----------|
| Source      | 00:03:01:F8:22:DD | 10.112.0.1 / 255.255.255.0 | 49184    |
| Destination | 00:03:01:FE:E4:BD | 10.112.0.100               | 7        |

|                     |          |
|---------------------|----------|
| EtherType           | 0x0800   |
| Automatic IP (DHCP) | Disabled |
| TTL                 | 128      |
| TOS                 | 0x00     |
| Default Gateway     | Disabled |

## FUNCTIONS

### Ping & Trace Route

| Network                |                       |
|------------------------|-----------------------|
| Source MAC Address     | 00:03:01:F8:22:DD     |
| Source IP Address      | 10.112.0.1 (Stream 1) |
| Destination IP Address | 0.0.0.0               |

| Ping                  |      |
|-----------------------|------|
| Timeout (ms)          | 4000 |
| Delay (ms)            | 1000 |
| Data Size (Bytes)     | 32   |
| TTL                   | 128  |
| Type Of Service (TOS) | 0x00 |

| Ping Results |            |                                               |
|--------------|------------|-----------------------------------------------|
| No.          | Status     | Reply Details                                 |
| 1            | Successful | IP=10.112.0.100, Bytes=32, Time=5 ms, TTL=127 |

| Ping Statistics              |     |
|------------------------------|-----|
| Packets Transmitted          | 1   |
| Packets Received             | 1   |
| Percentage Lost (%)          | 0.0 |
| Minimum Round Trip Time (ms) | 5   |
| Maximum Round Trip Time (ms) | 5   |
| Average Round Trip Time (ms) | 5   |

| Trace Route   |      |
|---------------|------|
| Timeout (ms)  | 4000 |
| Max Hop Count | 128  |

## SYSTEM INFORMATION

|                                   |                          |
|-----------------------------------|--------------------------|
| <b>Product Name</b>               | Power Blazer Series      |
| <b>Version</b>                    | Power Blazer Series 1.75 |
| <b>Module ID</b>                  | FTBx-8870                |
| <b>Slot ID</b>                    | 1                        |
| <b>Software Product Version</b>   | 1.75.0.85                |
|                                   | Power Blazer Series 1.75 |
| <b>Assembly Hardware Revision</b> | B                        |
| <b>Serial Number</b>              | 1343183                  |
| <b>Calibration Date</b>           | 4/20/2020 9:30:00 PM     |

## Pluggable Module

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>Module ID</b>            | SFP+                             |
| <b>Vendor Name</b>          | WFS                              |
| <b>Part Number</b>          | 10GB-SFP-LR-JN                   |
| <b>Serial Number</b>        | WFJNXPL917                       |
| <b>Hardware Revision</b>    | 1.0                              |
| <b>Connector Type</b>       | LC                               |
| <b>Speed</b>                | 10G                              |
| <b>Type/Compliance Code</b> | LR, 10.0 km (SMF)                |
| <b>Wavelength</b>           | 1310 nm                          |
| <b>Mode</b>                 | Single-Mode Fiber                |
| <b>Power Class</b>          | Power Class 1 Module (<= 1W max) |
| <b>Temperature (Max)</b>    | 26.5 °C                          |

## Software Options

|         |                             |          |
|---------|-----------------------------|----------|
| DS1-FDL | DS1/1.5M Facility Data Link | Disabled |
|---------|-----------------------------|----------|

|                 |                                                             |          |
|-----------------|-------------------------------------------------------------|----------|
| CPRI-10.1G      | CPRI 10.1376 Gbit/s                                         | Disabled |
| SDH             | Synchronous Digital Hierarchy                               | Enabled  |
| SONET           | Synchronous Optical Network                                 | Enabled  |
| 622M            | 622 Mbit/s                                                  | Disabled |
| eCPRI-10G       | eCPRI over 10G Ethernet                                     | Disabled |
| DSn             | Digital Signal (DS1, DS3)                                   | Disabled |
| PDH             | Plesiochronous Digital Hierarchy (E1, E3, E4)               | Disabled |
| 155M            | 155 Mbit/s                                                  | Disabled |
| 2488M           | 2.488 Gbit/s                                                | Disabled |
| 10G_LAN         | Ethernet 10G LAN optical interface                          | Enabled  |
| 10G_WAN         | Ethernet 10G WAN optical interface                          | Enabled  |
| L2-Transparency | L2CP Handling Test in EtherSAM                              | Disabled |
| TCM             | Tandem Connection Monitoring HO/LO                          | Disabled |
| G82752          | ITU-T G.8275.2 Profile                                      | Disabled |
| TunableOptics   | Tunable Wavelength Support for SFP+                         | Disabled |
| 9953M           | 9.953 Gbit/s                                                | Disabled |
| OTU1            | Optical Transport Unit-1 (2.7 Gbit/s)                       | Disabled |
| OTU2            | Optical Transport Unit-2 (10.7 Gbit/s)                      | Disabled |
| 100optical      | Ethernet 100Base-FX (Optical) Interface                     | Disabled |
| GigE_Optical    | Ethernet 1000Base-X (Optical) Interface                     | Enabled  |
| GigE_Electrical | Ethernet 1000Base-T (Electrical) Interface                  | Enabled  |
| FC-1X           | Fibre Channel 1X                                            | Disabled |
| FC-2X           | Fibre Channel 2X                                            | Disabled |
| TCP-THPUT       | Tcp Throughput Test Application                             | Disabled |
| 100electrical   | Ethernet 100Base-TX (Electrical) Interface                  | Enabled  |
| 10electrical    | Ethernet 10Base-T (Electrical) Interface                    | Enabled  |
| ODUMUX          | ODU Multiplexing Payload Type 20 and 21                     | Disabled |
| FC-10X          | Fibre Channel 10X                                           | Disabled |
| OTU2-1e-2e      | Optical Transport Unit-2 Overclocked (11.049/11.096 Gbit/s) | Disabled |
| FC-4X           | Fibre Channel 4X                                            | Disabled |
| ADV-FILTERS     | Advanced Filtering                                          | Disabled |
| MPLS            | MPLS Encapsulation (10GE and less)                          | Disabled |
| IPV6            | Internet Protocol Version 6 (IPv6) (10GE and less)          | Disabled |
| OTN-INTR-THRU   | OTN Intrusive Through Mode                                  | Disabled |
| EoOTN           | Ethernet over Optical Transport Network                     | Disabled |
| ETH-THRU        | Through Mode Test Application                               | Disabled |
| OTU2-1f-2f      | Optical Transport Unit-2 Overclocked (11.270/11.317 Gbit/s) | Disabled |
| Cable_Test      | Cable Test                                                  | Disabled |
| ODU0            | OTN ODU0                                                    | Disabled |
| ETH-CAPTURE     | Ethernet Frame Capture for Advanced Troubleshooting         | Disabled |
| ODUflex         | OTN ODUflex                                                 | Disabled |
| TRAFFIC-SCAN    | Traffic Scan                                                | Disabled |
| 52M             | 52 Mbit/s                                                   | Enabled  |
| NI-CSU          | NI/CSU Emulation                                            | Disabled |
| FC-8X           | Fibre Channel 8X                                            | Disabled |
| CPRI            | CPRI 2.4576 Gbit/s and 3.072 Gbit/s                         | Disabled |

|                  |                                                        |          |
|------------------|--------------------------------------------------------|----------|
| OBSAI            | OBSAI 3.072 Gbit/s                                     | Disabled |
| 1588PTP          | 1588 Precision Time Protocol                           | Disabled |
| SyncE            | Synchronous Ethernet                                   | Disabled |
| ETH-OAM          | Carrier Ethernet OAM Test Application                  | Disabled |
| CPRI-1.2G        | CPRI 1.2288 Gbit/s                                     | Disabled |
| CPRI-4.9G        | CPRI 4.9152 Gbit/s                                     | Disabled |
| CPRI-6.1G        | CPRI 6.144 Gbit/s                                      | Disabled |
| CPRI-9.8G        | CPRI 9.8304 Gbit/s                                     | Disabled |
| DUAL-PORT        | Dual Port Test                                         | Disabled |
| RFC6349          | RFC 6349 Test Application (10GE and less)              | Disabled |
| iSAM             | Intelligent Service Activation Methodology             | Disabled |
| PoE              | Power Over Ethernet                                    | Disabled |
| LINK-OAM         | Link OAM                                               | Disabled |
| DP-CPRI          | Dual Port CPRI                                         | Disabled |
| TST-OAM          | Test Over Service OAM                                  | Disabled |
| G82751           | ITU-T G.8275.1 Profile                                 | Disabled |
| iOptics          | Intelligent Pluggable Optic Test Application           | Disabled |
| EoE              | Ethernet over Ethernet Encapsulation (10GE and less)   | Disabled |
| PBBTE            | Provider Backbone Bridge Encapsulation (10GE and less) | Disabled |
| RFC6349-EXFOWorx | Enables EXFO Worx Interop Operation Mode               | Disabled |
| GCC-BERT         | OTN Overhead BERT and Synchronization Validation       | Disabled |
| OBSAI-1.5G       | OBSAI 1.536 Gbit/s                                     | Disabled |
| OBSAI-6.1G       | OBSAI 6.144 Gbit/s                                     | Disabled |
| DTS-NAT          | NAT Traversal for DTS applications                     | Disabled |

## LOGGER

| ID | Start Time        | Event                    | Duration | Details                                                                                           |
|----|-------------------|--------------------------|----------|---------------------------------------------------------------------------------------------------|
| 1  | 09/03 10:50:54 AM | Test Started             |          | 2021-09-03                                                                                        |
| 2  | 09/03 10:50:58 AM | Service Configuration te |          | 2021-09-03                                                                                        |
| 3  | 09/03 10:51:27 AM | Service 1 Fail           |          | 1 Service 1                                                                                       |
| 4  | 09/03 10:51:33 AM | Service Performance tes  |          | 2021-09-03                                                                                        |
| 5  | 09/03 10:51:38 AM | Frame Loss               | 00:10:05 | 61988779/61988779 S(1)                                                                            |
| 6  | 09/03 10:51:38 AM | Latency > 28.0 ms        | 00:10:05 | 159.10768 ms S(1)                                                                                 |
| 7  | 09/03 11:01:42 AM | RX Rate < 9500.0 Mbit/   | 00:00:01 | 8830.91 Mbit/s S(1)                                                                               |
| 8  | 09/03 11:01:42 AM | Frame Loss > 1.0E-04     | 00:00:01 | 7.0E-02 S(1)                                                                                      |
| 9  | 09/03 11:01:42 AM | Service 1 Fail           |          | 1 Service 1                                                                                       |
| 10 | 09/03 11:01:42 AM | Test Stopped             |          |  <b>FAIL</b> |